


T9P Series Pivot Pad Carton Clamp



Hydraulic Requirements: Double function auxiliary kit

| Model No. | Capacity | @ LC | Range Inside Pads | Frame Width | Pad Reach | Pad Height | Weight | ET | HCG | VCG | Mtg |
|--------------|----------|------|-------------------|-------------|-----------|------------|--------|-----|------|------|-----|
| T9-35-30-48P | 3500 | 15 | 22 - 76 | 44 | 30 | 48 | 1214 | 5.5 | 8.6 | 15.3 | II |
| T9-35-36-48P | 3500 | 18 | 22 - 76 | 44 | 36 | 48 | 1327 | 5.5 | 10.0 | 15.4 | II |
| T9-35-42-48P | 3500 | 20 | 22 - 76 | 44 | 42 | 48 | 1435 | 5.5 | 11.6 | 15.5 | II |
| T9-35-45-48P | 3500 | 22 | 22 - 76 | 44 | 45 | 48 | 1489 | 5.5 | 12.4 | 15.5 | II |
| T9-35-48-48P | 3500 | 24 | 22 - 76 | 44 | 48 | 48 | 1543 | 5.5 | 13.2 | 15.5 | II |
| T9-35-52-48P | 3230 | 26 | 22 - 76 | 44 | 52 | 48 | 1615 | 5.5 | 14.3 | 15.6 | II |
| T9-35-54-48P | 3100 | 27 | 22 - 76 | 44 | 54 | 48 | 1651 | 5.5 | 14.8 | 15.6 | II |
| T9-35-60-48P | 2800 | 30 | 22 - 76 | 44 | 60 | 48 | 1758 | 5.5 | 16.4 | 15.7 | II |
| T9-35-48-60P | 2800 | 30 | 22 - 84 | 50 | 48 | 60 | 1870 | 5.5 | 13.4 | 16.0 | II |
| T9-35-40-48P | 2800 | 30 | 22 - 84 | 50 | 48 | 60 | 1398 | 5.5 | 11.6 | 15.5 | II |

Arms open and close equally and sideshift left or right

Maximum Pressure

2250 psi (150 bar)

Recommended Flow

6 gpm (27 litres)

Optional Auxiliary Hydraulics

- 3 way pressure reducing valve
- Variable pressure reducing valve
- Pressure gauge
- Quick disconnect couplings

Things we need to know...

- ✓ Weight of Load
- ✓ Max. Width of Load
- ✓ Min. Width of Load
- ✓ Height of Load
- ✓ Length of Load
- ✓ Type of Product
- ✓ Forklift Capacity